



UV DTF Printer		
Model	W2070-3(I1600)	
Print width	30cm	
Main Board	Hoson Board	
Print head	2pcs Epson I1600-A1	
Color	CMYK+White+Varnish	
Ink	UV Ink	
White Ink	White ink automatic mixing system	
	6 Pass	1.38m ² /hour
	8 Pass	0.88 m ² /hour
Guide	Hinwin	
UV LED Light	high-power UV lamp, more stable curing effect, 2pcs lamps	
Cooling system	Air cooling system	
Carriage	Auto up and down carriage	
Ink supply system	CISS Continuously Ink Supply System.White Ink Circulation System	
Operation Environment	Temperature:18-35℃ , Humidity:40RH-70RH	
Medium type	FILM A+Film B	
Ink shortage alarm	Equipped	
Waste film collection	the swing rod is tensioned to collect waste film intelligently	
Connector	Network	
Language	English/ Chinese	
Rip Software	Photoprint 19	
Laminator	High-precision rubber roller, intelligent temperature control rubber roller heating	



Unwinding system	Resistance double-sided adjustable unwinding system
Power consume	1200W
Driven system	Windows xp, win 7 32bit/64bits/Win8/Win 10
Power supply	220V 50-60HZ (110V, option)
Equipment Size	1200mm×500 mm×1166 mm
Packing size	1525 mm ×725 mm ×755 mm
GW/NW	130KG/100KG
Warranty	1 year (except printhead and ink supply system)
PVP	Consultar oferta
Consumibles Precio	Ink price: /L
	Film A: roll, 30cm*100m per roll
	Film B:roll,30cm*100m per roll
Condiciones de Pago	Contado